



EVERUN AFRICA

ELECTRIC WHEEL LOADER

ERELO5



Optional DC battery system and AC battery system, with zero-pollution.



Passed CE quality certification.



The small size can work in a small limited space, and is flexible in operation.



Multi-options for attachments.



Standard configuration with Quick Hitch and Electric Joystick, easier to operate.



Lifting Height - 2100mm



Maintenance-Free Batteries makes later use more convenient and more secure.



Rated Load - 500kg



Performance:

Rated Load	500kg
Bucket Rated Capacity	0.2m ³
Dumping Height at 40°	1300mm
Lifting Height	2100mm
Dumping Reach	550mm
Max. Lifting Weight	500kg
Max. Excavation Force	8kN
Max. Grade Ability	15
Max. Turning Angle	25° ± 1
Rear Axle Swing Degree	3°

Dimensions & Weight:

Overall Length	2836mm (Bucket on ground position)
Bucket Width (overall)	900mm
Overall Height	2110mm
Wheel Base	1385mm
Min. Ground Clearance	300mm
Net Weight	900kg

Battery:

Battery Model	No.6-EVF-100A (OR 120 AH OR 150AH)
Rated Capacity	(3hr) 100Ah4kW
No. Of Batteries	5
Rated Voltage	60V
Working Hours	4-8 HRS

Transmission System:

Hydraulic System	DC or AC
Motor Type	HL-60
Voltage	60V
Power	1500W
Displacement	16ml/r

Steering System:

External Gear Pump	1pc
Steering Cylinder Bore	50mm
System Pressure	16MPa

Braking System:

Service Brake	Drum Brake
Brake Drum	200mm
Parking Break	Drum Brake
Distribution Valve Model	DL10 Type - Triple valve system
Dumping Cylinder Bore	Ø50
Lifting Cylinder Bore	Ø50

Tyres:

Type	6.00 -12
Working Pressure	0.025MPa
Qty	4

Oil Capacity:

Hydraulic Oil Tank	11L
Brake Fluid	0.8L

EVERUN AFRICA

